

# BE-6801

## 8-port VGA KVM Switch




The BE-6801 is a VGA Combo KVM Switch, can control multiple servers and computers from a single console. It features daisy chain, OSD (On Screen Display) menu, password security, hotkey control, push button and auto-scan control, as well as complete keyboard/mouse emulation.


### Features:

- ❖ 8-port combo KVM Switch.
- ❖ Support one local console.
- ❖ Support Microsoft Windows, Netware Unix and Linux.
- ❖ Support imac, Power MAC and Sun Micro Systems with USB port.
- ❖ No software required: easy computer selection via OSD menu, push buttons and hotkeys.
- ❖ Selectable hotkeys: Scroll/Caps/Num-Lock, Alt, Ctrl, Win.
- ❖ Support two levels of password security protections.
- ❖ Provide ACL (Access Control List) security function; store up to 8 independent ACLs of controllable computer lists.
- ❖ Hot Plug: add or remove connected computers without power off the KVM Switch or computers.
- ❖ Plug-n-Play monitor support.
- ❖ Keyboard status restored when switching computers.
- ❖ Support daisy chain up to 8 layers.

# Front View




# Rear View



## Specifications:

Model No.	BE-6801
Host Port Connector	VGA + PS2 or VGA + USB
Combo VGA	8
Console Type	PS/2 or USB
Max. Distance (KVM Switch -- Host)	16 feet (5m)
Max. Video Resolution (Local Console)	1920 x 1440
Flash Port (Firmware Upgrade)	DC2.5F
Daisy Chain	Connector DB15 (Female Type)
	Support daisy chain up to 8 layers
Computers Selection	On Screen Display (OSD) Menu, Hotkey, Push Button
Hotkey	Scroll-Lock/ Caps-Lock/ Num-Lock/ Alt/ Ctrl/ Win
Computer Port LEDs	2 LEDs for each host port: ON LINE (Yellow), SATATION (Red)
Security	Provide ACL (Access Control List) security function, store up to 8 independent ACL's of controllable computer lists
Multilingual OSD (On Screen Display)	8 languages (English, France, Germen, Spanish, Italian, Russian, Japanese, Chinese)
Auto-Scan Intervals	5 ~ 99 Sec.
Keyboard Emulation	USB
Mouse Emulation	USB
Max. Connected Computers	Up to 128 computers (16-port model * 8 layers)
Housing Material	Metal
DC Power Adapter	12V, 1A
Operation Temperature	0 ~ 50 °C
Storage Temperature	-20 ~ 60 °C
Humidity	0~80%, Non-Condensing
Mechanical	19" Rack mount, 1U
Dimension (mm)	444.5 x 190 x 44

# Diagram



# OSD Menu

M A I N M E N U					X
S E L E C T O P T I O N :					
0 1	L A N G U A G E				
0 2	P O R T	N A M E	E D I T		
0 3	P O R T	S E A R C H			
0 4	U S E R	S E C U R I T Y			
0 5	A C C E S S	L I S T			
0 6	H O T K E Y				
0 7	T I M E	S E T T I N G S			
0 8	O S D	M O U S E			