

K305114MRS


Single PC Multiple access CAT5 KVM Extender

The K305114MRS is a CAT5 VGA KVM Extender for one PC with multiple accesses. It includes BE-114MRS (4-port VGA with RS232 CAT5 KVM Transmitter) and BE-6305MRS (VGA with RS232 CAT5 KVM Receiver). Using advanced CAT5e cable technology, one PC can be accessed from 4 (or 8) users. The receivers can be placed up to 150/300 meters away from the transmitter.



Features


- ❖ UTP maximum cable length: 150 or 300 meters depending on BE-6305MRS.
- ❖ UTP Cable type: CAT5e, EIA/TIA 568B.
- ❖ Console keyboard/mouse: USB and PS2.
- ❖ Video resolution: max. 1600 x 1200 @ 60Hz depends on cable quality.
- ❖ EDID: Learning from BE-114MRS's local monitor.
- ❖ RS-232: 9600, 8-n-1, non flow control.
- ❖ Multiple Console Access: Sharing mode and Exclusive mode.
- ❖ All BE-114MRS and BE-6305MRS are firmware upgradable.
- ❖ RJ45 pin assignments: straight through pin-to-pin, with pairing.



Specification

K305114MRS			
Model No.	BE-114MRS	BE-6305MRS-150/300	
	Transmitter	Receiver	
System Cable	CAT5e, Solid Wire 2x4x24 AWG, standard 568B RJ-45 connector		
Connectors	System Out	4 x RJ45 Female	X
	System In	X	1 x RJ45 Female
	Keyboard		1 x PS2 1 x USB Type A
	Mouse		1 x PS2 1 x USB Type A
	USB-to-PC	1 x USB Type A	
	VGA In	1 x HDD15 Female	X
	VGA Out	1 x HDD15 Female	1 x HDD15 Female
	RS-232	1 x DB-9	1 x DB-9
	Power In:	1 x AC, 60Hz/50Hz	1 x DC Jack
Power LED	1 (Green)		
Video Gain/EQ	X	2 x Mini Port	
Video	1600 x 1200 @ 60Hz, DDC2B		
Maximum Distance	Depends on receiver, and CAT5 cable quality. 0~300M		
Dimensions	21.3L x 13.4W x 4.4H cm	14L x 9.3W x 3.2H cm	
Weight	860g	380g	

Diagram



Ordering Information

BE-6305MRS-150	150m CAT5 VGA with RS232 KVM Receiver
BE-6305MRS-300	300m CAT5 VGA with RS232 KVM Receiver
BE-114MRS	4-port CAT5 VGA with RS232 KVM Transmitter
BE-118MRS	8-port CAT5 VGA with RS232 KVM Transmitter