

# BE-962b

## IP based Dual Head KVM Extender *over* UTP and SFP Fiber

The BE-962b is an IP Unicast based solution that extends Dual head of 4K30 with USB and 3.5mm audio, plus 2-way RS-232 across CAT6 cable up to 150M in 1080p/100M in 4K30, or SFP Fiber Module up to 10KM with SM/300M with MM SFP.



The extender contains a Transmitter unit and a Receiver unit. Based on Gigabit Ethernet transceiver physical layer with adopt visually lossless video compression algorithm technology, the device achieves razor sharp video quality and robust performance in noisy environment.

### Features

- Support Dual Head 4K30, 1920x1200@60Hz resolution with Low Latency Time.
- Support IP based Gigabit Ethernet Switch for physical layer transmission, built in both RJ-45 and SFP connection.
- Support 8 x USB 2.0 ports for keyboard, mouse, touch, storage.
- Support bi-directional 3.5mm audio, speaker and microphone at Receiver site.
- Support Auto EDID from Rx screen.
- Pure hardware design, plug-and-play, no additional software installation is required.



BE-962b Tx Front and Rear panel



BE-962b Rx Front and Rear panel

## Specification

Model No.		BE-962bT Transmitter	BE-962bR Receiver
Connectors	HD 1.4 In	2	N/A
	HD 1.4 Out	N/A	2
	IR (option)	Yes	
	USB	2 x USB-B to PC upstream	8 x USB-A to devices
	3.5mm Audio	2 x Line-In and 2 x Line-Out	2 x Line-Out and 2 x Mic-In
	Power	AC 100 ~ 240V	
	System port	2 x RJ45 and 2 x SFP	
	RS-232	3-pin terminal connector, maximum baud rate 115200 bps	
Resolution		Maximum 4K30	
Inter-connect Cable		CAT 6/7 or SM/MM Fiber cable	
Power consumption		RJ45 ≤ 240mA/SFP ≤ 220mA	RJ45 ≤ 160mA/SFP ≤ 200mA
Environment	OP Temperature	0 ~ 55°C	
	ST Temperature	-20 ~ 85°C	
	Humidity	5 ~ 90% Non-condensing	
Physical Properties	Material	Metal with standard 100 x 100 VESA mount support	
	Weight	1350 g	950 g
	Dimension (L x W x H)	438 x 85 x 44 mm	240 x 85 x 48 mm