BE-1708A1-H



8-Port 17.3" LCD/HDMI KVM Switch







Cascade Port



LCD KVM features:

No	Part	Function Description
1	Handle	Pull this handle to pull out the KVM module; push this handle to push back the KVM module.
2	LCD display	Support Auto power ON/OFF while opening & closing the monitor if there is certain degree angle ,supporting DDC/DDC2B
3	LCD control button	LCD switch button and control LCD screen position and image setting.
4	Keyboard	Support keyboard with backlight for typing comfort.
5	Touchpad	
6	LED	Power indicator
7	Rack bracket	The rack is at the two sides of the equipment, used to fix the bottom of the equipment on the rack.
8	Lock and indicating lamps	Indicating lamp of Num Lock, Caps Lock and Scroll Lock respectively.
9	Buckle	Push in this buckle before the console can be pushed and pulled freely on the rack.
10	Supports 19" rack mounting kit	

Specifications

Model No	BE-1708A1-H(17.3"LCD)
Display Size	17.3"
Panel Type	SXGA TFT
Resolution	1920x1080@60Hz
PC Port	8
Best control distance	5m
Interface Attribute	HDMI
Keyboard	Standard 104 Keyboard
Mouse	Touchpad with two button
Operation	By OSD,HotKey,Panel
Angle of visibility	80/80/60/80(Typ.)(CR≥10)
Brightness	400 cd/ m^2 (Typ.)
Contrast	600:1(Тур.)
Power Consumption	15W
Power Supply	AC100∼240V 50∼60Hz
Operation Tempture	0°C ~50°C
Storage Tempture	-20°C ~60°C
Humidity	0~80%RH
Weight	11.5kg
Dimension(DxWxH)	500mmx450mmx42mm

Ordering Information

DE 1700A1 II	Q Dowt 17 2"I CD /I IDMI KV/M Constab
BE-1708A1-H	8-Port 17.3"LCD /HDMI KVM Switch